

VF-2 and VF-3 Ventless Fryers

The compact ventless fryers with the proven round well cooking design engineered for consistent heat distribution, durability, and efficiency.

These compact ventless fryers fit on virtually any countertop. More importantly, they are self-venting, so there is no costly installation of expensive hoods and vents (check your local restrictions, requirements vary). They even have built-in fire suppression systems and resettable high temp limit switches for added safety.



VF-3

VF-2

Both models are easy to operate with an autolift feature that raises and lowers the lift basket in the cooking well automatically and our handy Temp-N-Time™ feature that allows any one of 10 preset time and temperature combinations to be recalled with the touch of a button.

Dimensions (approximate)

Model	Width	Height	Depth	Ship Wt.	Capacity
VF-2	19"	24"	18-3/4"	140 lbs.	2 lbs./load (.91 kg/load)
VF-3	25"	27-1/2"	23"	180 lbs.	3 lbs./load (1.36 kg/load)

Electrical Specifications

120/208V, 1 Ph, 60 Hz - 26.5 amps or 120/240V, 1 Ph, 60 Hz - 23.0 amps, 4 wire with ground and neutral

ETL and ETL Sanitation listed and certified in accordance with UL197, UL710B, CSA C22.2 No. 109-M, and ANSI/NSF4.



VF Accessory Kit

5-Gallon Drain Bucket & Cover, Crumb Strainer, Pouring Cup, PVC Jersey Lined Gloves, Poly Gloves, Cleaning Sponge, Short Tongs, Thermometer, Spatula